

HS-B62I40-MPF

2MP LightHunter HD IR Fixed Mini Bullet Analog Camera



قابلیت های کلیدی

- نور مادون قرمز 40 تا 60 متر
- کاهنده نویز دیجیتال 3D

- دارای میکروفون
- OSD قابل تنظیم

- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

Pixel	2MP
Sensor Size	1/2.9"
Min. Illumination	0.005 lux (F1.6, AGC ON) 0 lux (IR on)
Focus	UAC-B122-AF28LM:2.8mm UAC-B-122AF40LM:4.0mm
Lens Mount	M12
Angle of View (H)	UAC-B122-AF28LM:101.5° UAC-B122-AF40LM:83.8°
Angle of View (V)	UAC-B122-AF28LM:56.9° UAC-B122-AF40LM:42.7°
Angle of View (D)	UAC-B122-AF28LM:117.4° UAC-B122-AF40LM:100.1°
Illuminator Number	Two IR illuminators
Illumination Distance	40m
Lifetime	>60000 hours
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)
Frame Rate	TVI/AHD/CVI: 1080P@25fps(default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC
Shutter Time	PAL: 1/25s- 1/50000s, NTSC: 1/30s- 1/50000s
Exposure Mode	Four modes: Global(default), BLC, HLC, DWDR
Day/Night	Three modes: Auto(default), Day, Night
Digital Noise Reduction	2D/3D

White Balance	Two modes: Auto (default), Manual
WDR	DWDR
Smart IR	Support
Flip	Supports 180° horizontal flip, 180° vertical flip
Digital Defog	Support
Built-in Mic	Support
Camera Audio	TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps
Power Interface	5.5mm Power Interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS
Temperature	- 30 °C to 60 °C (-22 ° F to 140 ° F)
Humidity	≤95% RH (non-condensing)
Surge Protection	4KV for power; 4KV for video output interfaces
Ingress Protection	IP67
Power	DC12V± 25%
Power Consumption	MAX 3.2W
Mount	Corner Mount; Pole Mount
Dimensions	154mm*66mm*66mm (L*W*H)
Material	Metal+Plastic
Weight	240g(0.53lb)

Dimensions

