

HS-B62L20-PF

2MP ColourHunter Fixed Bullet Analog Camera



قابلیت های کلیدی

- دمای کارکرد 30- تا 60+ درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت
- دارای میکروفون
- OSD قابل تنظیم
- تصویر رنگی 24/7
- نور مرئی تا 20 متر
- کاهنده نویز دیجیتال 3D

Specifications

Pixel	2MP
Sensor Size	1/3"
Min. Illumination	0.01 lux (F1.6, AGC ON) 0 lux (white light on)
Focus	UAC-B112 - AF28-W:2.8mm UAC-B112-AF40-W:4.0mm
Lens Mount	M12
Angle of View (H)	100.9°
Angle of View (V)	56.5°
Angle of View (D)	121.8°
Illuminator Number	One white-light illuminator
Illumination Distance	20m
Lifetime	≥60000 hours
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H)×720(V)
Frame Rate	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC
Shutter Time	PAL: 1/25s- 1/50000s, NTSC: 1/30s- 1/50000s
Exposure Mode	Four modes: Global(default),BLC,HLC,DWDR
Day/Night	24/7 color images
Digital Noise Reduction	2D/3D
OSD menu language	11 Languages English, German, Spanish(Latin America), French, Italian, Japanese, Korean, Polish, Portuguese(Brazil), Russian, Turkish
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B)

White Balance	Two modes: Auto (default), Manual
WDR	DWDR
Flip	Supports 180° horizontal flip, 180° vertical flip
Digital Defog	N/A
Built-in Mic	Support
Camera Audio	TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps
Power Interface	5.5mm Power Interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS
Temperature	- 30°C to 60 °C (- 22 ° F to 140 ° F)
Humidity	≤95 % RH (non-condensing)
Surge Protection	4kV for power & 4kV for video output interfaces
Power	DC12V± 25 %
Power Consumption	MAX 2.3W
Mount	Corner Mount & Pole Mount
Dimensions	142mm*63mm*65mm (L*W*H)
Material	Graphene+Plastic
Weight	146g(0.32lb)
Safety	CE-LVD (EN 1-62368)
Environment	CE-RoHS (2011/65/EU; EU863/2015); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)

Dimensions

