

HS-B65I20-PF

5MP HD Fixed IR Mini Bullet Analog Camera



قابلیت های کلیدی

- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالتی
- OSD قابل تنظیم
- نور مادون قرمز 20 تا 40 متر
- کاهنده نویز دیجیتال 3D

Specifications

Pixel	5MP
Sensor Size	1/2.7"
Min. Illumination	0.02 lux (F2.0, AGC ON) 0 lux (IR on)
Focus	2.8mm
Lens Mount	M12
Angle of View (H)	102.2°
Angle of View (V)	63.9°
Angle of View (D)	124.8°
Illuminator Number	One IR illuminator
Illumination Distance	20m
Lifetime	≥60000 hours
Frame Rate	TVI: 5MP@20fps(default), 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVBS: PAL/NTSC
Shutter Time	PAL: 1/25s 1/50000s, NTSC: 1/30s - 1/50000s
Exposure Mode	Four modes: Global(default),BLC,HLC,DWDR
Day/Night	Three modes: Auto(default),Day,Night
Digital Noise Reduction	2D

Resolution	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V) 4MP: 2560(H)×1440(V) 1080P: 1920(H)×1080(V)
White Balance	Two modes: Auto (default),Manual
WDR	DWDR
Smart IR	Support
Flip	Supports 180° horizontal flip, 180° vertical flip
Power Interface	5.5mm Power Interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS
Temperature	- 30 °C to 60 °C (- 22 ° F to 140 ° F)
Humidity	≤95 % RH (non-condensing)
Surge Protection	4KV for power;4KV for video output interfaces
Ingress Protection	IP67
Power	DC12V± 25 %
Power Consumption	MAX 3.6W
Mount	Corner Mount;Pole Mount
Dimensions	142mm*63mm*65mm (L*W*H)
Material	Plastic
Weight	135g(0.30lb)

Dimensions

