

HS-T62I20-PF

2MP Fixed IR Turret Analog Camera



قابلیت های کلیدی

- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- قابلیت شب و روز
- IR هوشمند 20 تا 40 متر
- کاهنده نویز دیجیتال 3D

Specifications

Pixel	2MP	White Balance	Two modes: Auto (default), Manual
Sensor Size	1/3"	WDR	DWDR
Min. Illumination	0.02 lux (F2.0, AGC ON) 0 lux (IR ON)	Smart IR	Support
Focus	2.8mm	Flip	Supports 180° horizontal flip, 180° vertical flip
Lens Mount	M12	Digital Defog	N/A
Angle of View (H)	90.5°	Built-in Mic	Support
Angle of View (V)	49.6°	Camera Audio	TVI: 5MP@20fps, 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps
Angle of View (D)	109.6°	Power Interface	5.5mm Power Interface
Illuminator Number	One IR illuminator	Video Output	BNC, supports TVI/AHD/CVI/CVBS
Illumination Distance	20m	Temperature	-30°C to 60°C (-22 °F to 140 °F)
Lifetime	≥60000 hours	Humidity	≤95% RH (non-condensing)
Frame Rate	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC	Surge Protection	4KV for power; 4KV for video output interfaces
Shutter Time	PAL: 1/25s 1/50000s, NTSC: 1/30s - 1/50000s	Power	DC12V±25%
Exposure Mode	Four modes: Global(default), BLC, HLC, DWDR	Power Consumption	MAX 2.2W
Day/Night	Three modes: Auto (default), Day, Night	Mount	Wall Mount, Pole Mount, Corner Mount, Pendant Mount
Digital Noise Reduction	2D/3D	Dimensions	Φ118mm*96mm (diameter*height)
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H)×720(V)	Material	Plastic
OSD menu language	11 Languages English, German, Spanish(Latin America), French, Italian, Japanese, Korean, Polish, Portuguese(Brazil), Russian, Turkish	Weight	182g(0.40lb)
Environment	CE-RoHS (2011/65/EU; EU2015/863); WEEE (2012/19/EU)	EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part 15 B)
		Safety	CE-LVD (EN 62368-1)
		Protection	IP67 (IEC 60529)

Dimensions

