

HS-T62I40-MPF

2MP LightHunter HD IR Fixed Turret Analog Camera



قابلیت های کلیدی

- دمای کارکرد 30- تا 60+ درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- قابلیت شب و روز
- IR هوشمند 40 تا 60 متر
- کاهنده نویز دیجیتال 3D

Specifications

Focus	2MP	White Balance	Two modes: Auto (default), Manual
Pixel	1/2.9"	WDR	DWDR
Sensor Size	0.005 lux (F1.6, AGC ON) 0 lux (IR on)	Flip	Supports 180° horizontal flip, 180° vertical flip
Min. Illumination	2.8 mm	Digital Defog	Support
Lens Mount	M12	Built-in Mic	Support
Angle of View (H)	101.5°	Camera Audio	TVI: 5MP@20fps, 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps
Angle of View (V)	56.9°	Power Interface	5.5mm Power Interface
Angle of View (D)	117.4°	Video Output	BNC, supports TVI/AHD/CVI/CVBS
Illuminator Number	Two IR illuminator	Temperature	- 30° C to 60° C (-22° F to 140° F)
Illumination Distance	40m	Humidity	≤95% RH (non-condensing)
Lifetime	≥60000 hours	Surge Protection	4KV for power; 4KV for video output interfaces
Frame Rate	TVI/AHD/CVI: 1080P@25fps(default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC	Power	DC12V± 25%
Shutter Time	PAL: 1/25s - 1/50000s, NTSC: 1/30s - 1/50000s	Power Consumption	MAX 3.2W
Exposure Mode	Four modes: Global(default), BLC, HLC, DWDR	Mount	Wall Mount; Pole Mount; Corner Mount; Pendant Mount
Day/Night	Three modes: Auto (default), Day, Night	Dimensions	Φ111mm*98mm (diameter*height)
Digital Noise Reduction	2D/3D	Material	Metal+plastic
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)	Weight	334g(0.74lb)
		Ingress Protection	IP67
		Smart IR	Support

Dimensions

