

HS-T62L20-PF

2MP ColourHunter Fixed Turret Analog Camera



قابلیت های کلیدی

- نور مرئی 20 تا 40 متر
- کاهنده نویز دیجیتال 3D
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- تصویر رنگی 24/7

Specifications

Pixel	2MP	White Balance	Two modes: Auto (default), Manual
Sensor Size	1/3"	WDR	DWDR
Min. Illumination	0.01 lux (F1.6, AGC ON) 0 lux (white light on)	Flip	Supports 180° horizontal flip, 180° vertical flip
Focus	2.8 mm	Digital Defog	N/A
Lens Mount	M12	Built-in Mic	Support
Angle of View (H)	100.9°	Camera Audio	TVI: 5MP@20fps, 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps
Angle of View (V)	56.5°	Power Interface	5.5mm Power Interface
Angle of View (D)	121.8°	Video Output	BNC, supports TVI/AHD/CVI/CVBS
Illuminator Number	One white-light illuminator	Temperature	- 30°C to 60°C (-22 ° F to 140 ° F)
Illumination Distance	20m	Humidity	≤95% RH (non-condensing)
Lifetime	≥60000 hours	Surge Protection	4KV for power; 4KV for video output interfaces
Frame Rate	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC	Power	DC12V± 25 %
Shutter Time	PAL: 1/25s - 1/50000s, NTSC: 1/30s - 1/50000s	Power Consumption	MAX 2.3W
Exposure Mode	Four modes: Global(default), BLC, HLC, DWDR	Mount	Wall Mount; Pole Mount; Corner Mount; Pendant Mount
Day/Night	24/7 color images	Dimensions	Φ118 mm * 96mm (diameter*height)
Digital Noise Reduction	2D/3D	Material	Graphene+Plastic
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)	Weight	209g(0.46lb)
OSD menu language	11 Languages English, German, Spanish(Latin America), French, Italian, Japanese, Korean, Polish, Portuguese(Brazil), Russian, Turkish	Safety	CE-LVD (EN 1-62368)
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2 , EN 55035) FCC (FCC 47 CFR part15 B)	Environment	CE-RoHS (2011/65/EU; EU)2015/863; WEEE (2012/19/EU)
		Protection	IP67 (IEC 60529)

Dimensions

