

## HS-T65I20-PF

5MP Fixed IR Turret Analog Camera



### قابلیت های کلیدی

- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- قابلیت شب و روز
- IR هوشمند 20 تا 40 متر
- دارای میکروفون داخلی

### Specifications

|                         |                                                                                                                                                                                                                                     |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pixel                   | 5MP                                                                                                                                                                                                                                 |
| Sensor Size             | 1/2.7"                                                                                                                                                                                                                              |
| Min. Illumination       | 0.02 lux (F2.0, AGC ON) 0 lux (IR ON)                                                                                                                                                                                               |
| Focus                   | 2.8 mm                                                                                                                                                                                                                              |
| Lens Mount              | M12                                                                                                                                                                                                                                 |
| Angle of View (H)       | 102.2°                                                                                                                                                                                                                              |
| Angle of View (V)       | 53.9°                                                                                                                                                                                                                               |
| Angle of View (D)       | 124.8°                                                                                                                                                                                                                              |
| Illuminator Number      | One IR illuminator                                                                                                                                                                                                                  |
| Illumination Distance   | 20m                                                                                                                                                                                                                                 |
| Lifetime                | >60000 hours                                                                                                                                                                                                                        |
| Frame Rate              | TVI: 5MP@20fps (default), 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps AHD: 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVI: 5MP@25fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVBS: PAL, NTSC |
| Shutter Time            | PAL: 1/25s - 1/50000s, NTSC: 1/30s - 1/50000s                                                                                                                                                                                       |
| Exposure Mode           | Four modes: Global(default), BLC, HLC, DWDR                                                                                                                                                                                         |
| Day/Night               | Three modes: Auto (default), Day, Night                                                                                                                                                                                             |
| Digital Noise Reduction | 2D                                                                                                                                                                                                                                  |
| Resolution              | 5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V) 4MP: 2560(H)×1440(V) 1080P: 1920(H)×1080(V)                                                                                                    |
| OSD menu language       | 11 Languages English, German, Spanish(Latin America), French, Italian, Japanese, Korean, Polish, Portuguese(Brazil), Russian, Turkish                                                                                               |
| EMC                     | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B)                                                                                                                                               |

|                   |                                                                                                                  |
|-------------------|------------------------------------------------------------------------------------------------------------------|
| White Balance     | Two modes: Auto (default), Manual                                                                                |
| WDR               | DWDR                                                                                                             |
| Smart IR          | Support                                                                                                          |
| Flip              | Supports 180° horizontal flip, 180° vertical flip                                                                |
| Digital Defog     | N/A                                                                                                              |
| Built-in Mic      | Support                                                                                                          |
| Camera Audio      | TVI: 5MP@20fps, 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVI: 5MP@25fps, 4MP@25fps, 4MP@30fps |
| Power Interface   | 5.5mm Power Interface                                                                                            |
| Video Output      | BNC, supports TVI/AHD/CVI/CVBS                                                                                   |
| Temperature       | -30°C to 60°C (-22 °F to 140 °F)                                                                                 |
| Humidity          | ≤95% RH (non-condensing)                                                                                         |
| Surge Protection  | 4KV for power; 4KV for video output interfaces                                                                   |
| Power             | DC12V±25%                                                                                                        |
| Power Consumption | MAX 3.3W                                                                                                         |
| Mount             | Wall Mount; Pole Mount; Corner Mount; Pendant Mount                                                              |
| Dimensions        | Φ118mm*96mm (diameter*height)                                                                                    |
| Material          | Plastic                                                                                                          |
| Weight            | 183g(0.40lb)                                                                                                     |
| Safety            | CE-LVD (EN 62368-1)                                                                                              |
| Environment       | CE-RoHS (2011/65/EU; EU2015/863); WEEE (2012/19/EU)                                                              |
| Protection        | IP67 (IEC 60529)                                                                                                 |

### Dimensions

