

## HS-T65L20-PF

5MP ColourHunter Fixed Turret Analog Camera



### قابلیت های کلیدی

- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- دارای میکروفون داخلی
- تصویر رنگی 24/7
- نور مرئی 20 تا 40 متر

## Specifications

Pixel	5MP
Sensor Size	1/2.7"
Min. Illumination	0.01 lux (F1.6, AGC ON) 0 lux (white light on)
Focus	2.8 mm
Lens Mount	M12
Angle of View (H)	110.0°
Angle of View (V)	57.0°
Angle of View (D)	130.0°
Illuminator Number	One white-light illuminator
Illumination Distance	20m
Lifetime	>60000 hours
Frame Rate	TVI: 5MP@20fps (default), 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps AHD: 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVI: 5MP@25fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVBS: PAL, NTSC
Shutter Time	PAL: 1/25s - 1/50000s, NTSC: 1/30s - 1/50000s
Exposure Mode	Four modes: Global(default), BLC, HLC, DWDR
Day/Night	24/7 color images
Digital Noise Reduction	2D
Resolution	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V) 4MP: 2560(H)×1440(V) 1080P: 1920(H)×1080(V)
OSD menu language	11 Languages English, German, Spanish(Latin America), French, Italian, Japanese, Korean, Polish, Portuguese(Brazil), Russian, Turkish

EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part 15 B)
White Balance	Two modes: Auto (default), Manual
WDR	DWDR
Smart IR	Support
Flip	Supports 180° horizontal flip, 180° vertical flip
Digital Defog	N/A
Built-in Mic	Support
Camera Audio	TVI: 5MP@20fps, 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVI: 5MP@25fps, 4MP@25fps, 4MP@30fps
Power Interface	5.5mm Power Interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS
Temperature	-30° C to 60° C (-22° F to 140° F)
Humidity	≤95% RH (non-condensing)
Surge Protection	4KV for power; 4KV for video output interfaces
Ingress Protection	IP67
Power	DC12V±25%
Power Consumption	MAX 2.3W
Mount	Wall Mount; Pole Mount; Corner Mount; Pendant Mount
Dimensions	Ø118mm*96mm (diameter*height)
Material	Graphene+Plastic
Weight	210g(0.46lb)
Safety	CE-LVD (EN 1-62368)
Environment	CE-RoHS (2011/65/EU; EU2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)

## Dimensions

